

Issue Date: 22.03.2019 Last revised date: 18.06.2019

1/14

Supersedes Date: -

SAFETY DATA SHEET

1. Identification

Product identifier: DEGADUR® B 71

Other means of identification

Recommended use: binder for floor-coating Roller application or brushing Hand-mixing with intimate contact and only PPE available Wide dispersive indoor use resulting in inclusion into or onto a matrix Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Recommended restrictions: None known.

Manufacturer/Importer/Distributor Information

Company Name : Röhm GmbH

Product Stewardship Kirschenallee 64293 Darmstadt

Telephone : +49 6151 18 4076

E-mail : sds-info@roehm.com

Manufacturer

Emergency telephone number:

24-Hour Health Emergency : +49 6241 402 5280 (24h)

+49 6131 19 240 (24h)

2. Hazard(s) identification

According to Hazardous Product Regulations

Physical Hazards

Flammable liquids Category 2

Health Hazards

Acute toxicity (Oral)

Skin irritation

Category 5

Skin sensitizer

Category 1

Specific Target Organ Toxicity
Category 3¹

Single Exposure

Target Organs

1. Respiratory system

Environmental Hazards

Acute hazards to the aquatic

environment

Label Elements

000005050768 REG GHS 2020-02-21

Category 3



Issue Date: 22.03.2019 Last revised date: 18.06.2019

Supersedes Date: -

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Highly flammable liquid and vapor.

May be harmful if swallowed.

Causes skin irritation.

May cause an allergic skin reaction. May cause respiratory irritation.

Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

[electrical/ventilating/lighting/...] equipment. Use non-sparking tools. Take

action to prevent static discharges. Avoid breathing

dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear

protective gloves/eye protection/face protection.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use dry

sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a

well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/ container to an approved waste disposal plant.

Other hazards: Take precautionary measures against static discharges. The product

is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is exceeded, the product may

polymerize with heat evolution.

3. Composition/information on ingredients

Mixtures

Solution of an acrylic polymer in an acrylic acid ester



Issue Date: 22.03.2019 Last revised date: 18.06.2019

Supersedes Date: -

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Methyl methacrylate		80-62-6	>=50,0 - <70,0%
triethyleneglycol dimethacrylate		109-16-0	>=1,0 - <10,0%
N,N-bis-(2-hydroxypropyl)-p-toluidine		38668-48-3	>=0,1 - <1,0%
Triisodecylphosphite		25448-25-3	>=0,1 - <1,0%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

General information: Take off all contaminated clothing immediately. Medical treatment is

necessary if symptoms occur which are obviously caused by skin or eye

contact with the product or by inhalation of its vapours. Remove

contaminated, saturated clothing.

Inhalation: Move subject to fresh air and keep him calm. If feeling unwell seek

medical advice.

Skin Contact: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower]. Wash contaminated clothing before

reuse. If symptoms persist, call a physician.

Eye contact: Rinse thoroughly with plenty of water, also under the eyelids. If

symptoms persist, call a physician.

Ingestion: Do not induce vomiting. Call a physician immediately. Never give

anything by mouth to an unconscious person.

Personal Protection for First-

aid Responders:

Wear self-contained breathing apparatus.

Most important symptoms/effects, acute and delayed

Symptoms: Excessive or prolonged exposure can cause the following: Daze

Numbness Headache. Difficulty in breathing. loss of

3/14

consciousness

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No specific antidote known.

5. Fire-fighting measures



Issue Date: 22.03.2019 Last revised date: 18.06.2019

Supersedes Date: -

General Fire Hazards:

Vapours are heavier than air and can form an explosive mixture with air. Flammable liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint. Remove sources of ignition. Also keep emptied containers away from sources of heat and ignition. Keep out unprotected persons. In case of fire, remove the endangered barrels and bring to a safe place, if this can be done safely. Containers exposed to heat (fire) may build up pressure. Cool by splashing with water. Prevent fire extinguishing water from contaminating surface water or the ground water system. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:

foam Dry chemical. Carbon dioxide

Unsuitable extinguishing media:

High volume water jet

Specific hazards arising from the chemical:

May be released in case of fire: carbon monoxide, carbon dioxide, organic products of decomposition. Closed container may rupture if strongly heated. Vapours may form explosive mixtures with air. Combustible air-vapour mixtures are heavier than the air and spread along the floor. Ignition from a considerable distance is possible.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:

Keep away from sources of ignition - No smoking. Vapors are heavier than air. Flammable liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint.

Take action to prevent static discharges. In the event of fire, cool the endangered containers with water. Fire fighting must be carried out from a safe distance. Use explosion-proof equipment.

Special protective equipment for fire-fighters:

Wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Assure sufficient ventilation. Use personal protective clothing. Use breathing apparatus if exposed to vapours/dust/mist/aerosol. Keep away from open flames, hot surfaces and sources of ignition. Vapours can form explosive mixtures with air. Keep out unprotected persons. Avoid spark generation.

Methods and material for containment and cleaning up:

Larger quantities: Remove mechanically (by pumping). Use explosion-proof equipment! Smaller quantities and/or residues: Contain with absorbent material (e.g. sand, diatomaceous earth, acid absorbent, universal absorbent or sawdust). Dispose of in accordance with regulations.

Environmental Precautions: Prevent product from getting into drains/surface water/groundwater.



Issue Date: 22.03.2019 Last revised date: 18.06.2019

Supersedes Date: -

7. Handling and storage

Precautions for safe handling:

Keep away from sources of ignition - No smoking. Vapors are heavier than air. Flammable liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint.

Take action to prevent static discharges. In the event of fire, cool the endangered containers with water. Fire fighting must be carried out from a safe distance. Use explosion-proof equipment. Do not breathe vapors. Avoid contact with skin and eyes. Wash hands before breaks and immediately after handling the product. Safety shower and eye wash fountain should be available. When using do not eat, drink or smoke. Avoid inhalation. ingestion and contact with skin and eyes. Provide sufficient ventilation and exhaust at the workplace. Provide good room ventilation even at ground level (vapours are heavier than air). Keep container tightly closed. Open drum carefully as content may be under pressure. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Wash thoroughly after handling. Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Controll staff entry to working area. Training for staff on good practice. Recording of any 'near miss' situations. Regular cleaning of equipment and work area. Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)

Conditions for safe storage, including any incompatibilities:

Keep away from direct sunlight. Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat. Protect from the action of light. Keep containers tightly closed in a cool, well-ventilated place. Fill the container by approximately 90 % only as oxygen (air) is required for stabilisation. With large storage containers make sure the oxygen (air) supply is sufficient to ensure stability. Keep at temperature not exceeding + 30 °C. Keep locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (03 2016)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (03 2016)

Biological Limit Values

No biological exposure limits noted for the ingredient(s).

Appropriate Engineering Controls

For monitoring procedures refer for instance to "Empfohlene Analysenverfahren für Arbeitsplatzmessungen", Schriftenreihe der Bundesanstalt für Arbeitsschutz and "NIOSH Manual of Analytical Methods", National Institute for Occupational Safety and Health

5/14



Issue Date: 22.03.2019 Last revised date: 18.06.2019

Supersedes Date: -

Individual protection measures, such as personal protective equipment

General information: No data available.

Eye/face protection: tightly fitting goggles

Skin Protection

Hand Protection: Material: butyl rubber gloves

Break-through time: 66 min

Guideline: EN 374

Additional Information: Gloves should be replaced regularly, especially after extended contact with the product., For each work-place a suitable glove

type has to be selected.

Other: On handling of larger quantities: face mask, chemical-resistant boots and

apron

Respiratory Protection: Breathing apparatus in case of high concentrations if the limit values like

TLV are exceeded, when vapours or aerosols occur Respirator with filter for

organic vapour

Hygiene measures: Take off all contaminated clothing immediately. Store work clothing

separately. Follow the usual good standards of occupational hygiene. Clean

skin thoroughly after work; apply skin cream.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: colourless
Odor: ester-like

Odor Threshold: No data available. pH: Not applicable

Freezing point: -48 °C (methyl methacrylate)

Boiling Point: approx. 100 °C (1.013 hPa) 212 °F (1.013 hPa) **Flash Point:** 10 °C (DIN 51 755) (methyl methacrylate)

Evaporation Rate:No data available. **Flammability (solid, gas):**No data available.

Flammability Limit - Upper (%): 12,5 %(V) (methyl methacrylate)
Flammability Limit - Lower (%): 2,1 %(V) (methyl methacrylate)

Vapor pressure: 37,8 hPa (20 °C) (methyl methacrylate)

Vapor density (air=1): > 1 20 °C

Density: 1,01 g/cm3 (20 °C) (DIN 51757)

Relative density: No data available.

Solubility(ies)

Solubility in Water: approx. 21 g/l (20 °C)
Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Autoignition Temperature: The substance or mixture is not classified as self heating.

Decomposition Temperature: No decomposition if used as directed.



Issue Date: 22.03.2019 Last revised date: 18.06.2019

7/14

Supersedes Date: -

Kinematic viscosity: No data available.

Dynamic viscosity: approx. 200 mPa.s (23 °C)

Explosive properties:No data available.
Oxidizing properties:
No data available.

Other information

Dust Explosion Limit, Upper:(methyl methacrylate)Dust Explosion Limit, Lower:(methyl methacrylate)

Minimum ignition temperature: 430 °C (DIN 51794) (methyl methacrylate)

Self Ignition Temperature: The substance or mixture is not classified as self

heating.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: No decomposition if used as directed.

Possibility of hazardous

reactions:

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions. Vigorous polymerization is possible when heated /exposed to

heat.

Conditions to avoid: Heat and ignition sources, aging, contamination, oxygen free atmosphere.

Ultraviolet light. The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is exceeded, the

product may polymerize with heat evolution.

Incompatible Materials: Peroxides, amines, sulfur compounds, heavy metal ions, alkalis, reducing

agents and oxidizing agents.

Hazardous Decomposition

Products:

None when used as directed.

11. Toxicological information

Information on likely routes of exposure

Inhalation: Relevant route of exposure. Information on effects are given below.

Skin Contact: Relevant route of exposure. Information on effects are given below.

Eye contact: Relevant route of exposure. Information on effects are given below.

Ingestion: If handled correctly, not a relevant route of exposure. Information on effects

are given below.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: Headache. Dizziness.

Skin Contact: May cause skin irritation. May cause allergic skin reaction.

Eye contact: Causes serious eye irritation.



Issue Date: 22.03.2019 Last revised date: 18.06.2019

Supersedes Date: -

Ingestion: If handled correctly, not a relevant route of exposure. Information on effects

are given below.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Acute toxicity estimate: 2.778 mg/kg

Dermal

Product: Acute toxicity estimate: > 5.000 mg/kg

Inhalation

Product: No data available.

Specified substance(s):

Methyl methacrylate LC 50 (Rat): 29,8 mg/l

Vapour

The substance or mixture has no acute inhalation toxicity

Dusts, mists and fumes

triethyleneglycol Not toxic after single exposure

dimethacrylate No labelling requiredDusts, mists and fumes

N,N-bis-(2- The substance or mixture has no acute inhalation toxicity

hydroxypropyl)-p- Dusts, mists and fumesThe substance or mixture has no acute inhalation

toluidine toxicity

Vapour

Triisodecylphosphite LC 50 (Rat): > 12,6 mg/l

Dusts, mists and fumes

Vapour

Repeated dose toxicity

Product: No data available.

Specified substance(s):

Methyl methacrylate NOAEL (Rat, Inhalation(Vapour)): 25 ppm

NOAEL (Rat, Oral): 2000 ppm NOAEL (Rat, Oral): 1.000 mg/kg

triethyleneglycol dimethacrylate

000005050768 REG GHS 2020-02-21

8/14



Issue Date: 22.03.2019 Last revised date: 18.06.2019

9/14

Supersedes Date: -

Skin Corrosion/Irritation

Product: Contact with skin may cause irritations. The data are derived from the

evaluations or test results achieved with the individual substances.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Methyl methacrylate Local Lymph Node Assay, OECD TG 429 (Mouse): May cause sensitization

by skin contact.

triethyleneglycol dimethacrylate

Local Lymph Node Assay (Mouse): Skin sensitizer

N,N-bis-(2hydroxypropyl)-p-

toluidine

Not a skin sensitizer.

Triisodecylphosphite May cause sensitization by skin contact.

Carcinogenicity

Product: Contains no ingredient listed as a carcinogen (>0.1%).

Germ Cell Mutagenicity

In vitro

Product: No data available.

Specified substance(s):

triethyleneglycol Not classified

dimethacrylate

N, N-bis-(2-(OECD TG 471)negative

hydroxypropyl)-p-toluidine

In vivo

Product: No data available.

Specified substance(s):

triethyleneglycol Not classified

dimethacrylate

N,N-bis-(2-Ames test: negative

hydroxypropyl)-p-toluidine

Reproductive toxicity

Product: Contains no ingredient listed as toxic to reproduction (>0.1%).

Specific Target Organ Toxicity - Single Exposure No data available. **Product:**

Specified substance(s):

Methyl methacrylate Category 3 with respiratory tract irritation. triethyleneglycol Not classified

dimethacrylate



Issue Date: 22.03.2019 Last revised date: 18.06.2019

Supersedes Date: -

N,N-bis-(2- Not classified

hydroxypropyl)-p-toluidine

Triisodecylphosphite Not classified

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Specified substance(s):

Methyl methacrylate Not classified triethyleneglycol Not classified

dimethacrylate

N,N-bis-(2- Not classified

hydroxypropyl)-p-toluidine

Triisodecylphosphite Not classified

Target Organs

Specific Target Organ Toxicity - Single Exposure: Respiratory system

Aspiration Hazard

Product: Not relevant.

Other effects: There are no toxicological data available for the product as such. Avoid

contact with the skin and eyes and inhalation of the product vapours.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Methyl methacrylate LC 50 (Oncorhynchus mykiss (rainbow trout), 96 h): > 79 mg/l

NOEC (Danio rerio (zebra fish), 32 d): 9,4 mg/l literature

triethyleneglycol dimethacrylate LC 50 (Danio rerio (zebra fish), 96 h): 16,4 mg/l

N,N-bis-(2-hydroxypropyl)-p-

toluidino

toluidine

LC 50 (Danio rerio (zebra fish), 96 h): 17 mg/l

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Methyl methacrylate EC 50 (Daphnia magna (Water flea), 48 h): 69 mg/l

NOEC (Daphnia magna (Water flea), 21 d): 37 mg/l

N,N-bis-(2hydroxypropyl)-p-

toluidine

EC 50 (Daphnia magna (Water flea), 48 h): 28,8 mg/l

10/14

Chronic hazards to the aquatic environment:



Issue Date: 22.03.2019 Last revised date: 18.06.2019

11/14

Supersedes Date: -

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

triethyleneglycol dimethacrylate NOEC (Daphnia magna (Water flea), 21 d): 32 mg/l

Toxicity to Aquatic Plants

Product: No data available.

Specified substance(s):

Methyl methacrylate EC 50 (Selenastrum capricornutum (green algae), 72 h): > 100 mg/l

NOEC (Selenastrum capricornutum (green algae), 72 h): > 100 mg/l

triethyleneglycol EC 50 (Pseudokirchneriella subcapitata (green algae), 72 h): > 100 mg/l dimethacrylate NOEC (Pseudokirchneriella subcapitata (green algae), 72 h): 18,6 mg/l

N,N-bis-(2-hydroxypropyl)-p-

toluidine

EC 50 (Desmodesmus subspicatus (green algae), 72 h): 245 mg/l

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Methyl methacrylate (14 d, OECD Test Guideline 301C): 94 % rapidly biodegradable

triethyleneglycol dimethacrylate

(28 d): 85 % Readily biodegradable

N,N-bis-(2-

hydroxypropyl)-p-toluidine

(28 d, OECD TG 301 B): 39 % Inherently biodegradable

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: no evidence for hazardous properties

Partition Coefficient n-octanol / water (log Kow)

Product: Log Kow: No data available.

Mobility in soil: no specific test data available

Other adverse effects: Prevent substance from entering soil, natural bodies of water and sewer

systems.



Issue Date: 22.03.2019 Last revised date: 18.06.2019

12/14

Supersedes Date: -

13. Disposal considerations

Disposal methods: Waste is hazardous. It must be disposed of in accordance with the

regulations after consultation of the competent local authorities and the

disposal company in a suitable and licensed facility.

Contaminated Packaging: Contaminated packages must be emptied as good as possible. They may

then be recycled after proper cleaning. Packages that cannot be cleaned must be disposed of in the same way as the substance. Uncontaminated

packaging may be taken for recycling.

14. Transport information

International Regulations

IATA-DGR

UN/ID No. : UN 1866

Proper shipping name : Resin solution STABILIZED

Class : 3
Packing group : II
Labels : 3
Packing instruction (cargo : 364

aircraft)

Packing instruction : 353

(passenger aircraft)

IMDG-Code

UN number : UN 1866

Proper shipping name : RESIN SOLUTION STABILIZED

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. Regulatory information

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention



Issue Date: 22.03.2019 Last revised date: 18.06.2019

Supersedes Date: -

Not applicable

Kyoto protocol

Not applicable

Inventory Status:

Registration, Evaluation and Authorisation of

Chemicals (REACH):

preregistered, registered or exempted

US TSCA Inventory:

On or in compliance with the inventory

Canada DSL Inventory List:

On or in compliance with the inventory

Canada NDSL Inventory: Not on Inventory.

Australia AICS: On or in compliance with the inventory

Japan (ENCS) List: On or in compliance with the inventory

Korea Existing Chemicals Inv. (KECI): On or in compliance with the inventory

Philippines PICCS: On or in compliance with the inventory

China Inv. Existing Chemical Substances:

On or in compliance with the inventory

16.Other information, including date of preparation or last revision

Issue Date: 18.06.2019

Revision Date: 06.06.2019: ARGLO_SUBTYP06.06.2019: ARGLO_EXCOMP06.06.2019:

ARGLO_REG

Version #: 1.1

Further Information: The product is normally supplied in a stabilized form. If the permissible

storage period and/or storage temperature is exceeded, the product may

13/14

polymerize with heat evolution.

Revision Information: Changes since the last version are highlighted in the margin. This version

replaces all previous versions.



Issue Date: 22.03.2019 Last revised date: 18.06.2019

Supersedes Date: -

Disclaimer:

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.